

ML16/40

- Combination Lathe
- Swing: 17"
- Spindle Bore: 2.05"
- Control : 8200-B



Shown with options



MILLTRONICS USA
LET'S INVENT

SPECIFICATIONS:

CAPACITY:

X/Z Travels	11 / 44.5" (280 / 1130 mm)
Swing Over Bed	17" (440 mm)
Swing Over Gap	25.9" (658 mm)
Gap Distance	12.75" (320 mm)
Swing Over Cross Slide	7.48" (190 mm)

SPINDLE:

Spindle Nose	A2-5
Spindle Bore	2.05" (52 mm)
Spindle Range	100-4000 RPM
AC Spindle Motor	18/12 HP (13/9 kW)
Spindle Torque	124 ft-lbs (168 N.m)

TAILSTOCK:

Tailstock Quill Travel	6" (150 mm)
Tailstock Quill Diameter	2.55" (65 mm)
Tailstock Quill Taper	MT4

AUTOMATIC TURRET:

Number of Tools	8
Tooling Size	.75" (20 mm)
Boring Bar Capacity	1.25" (32 mm)
Tool Selection	Bi-directional

MOTION:

X/Y/Z Axis Rapid Traverse Rate	500 IPM (12.7 m/min)
Max. Cutting Feed Rate	100 IPM (2540 mm/min)
X Axis Ballscrew Diameter	1" (25 mm)
Y Axis Ballscrew Diameter	1.57" (40 mm)
Positioning Accuracy	+/- 0.00025" (+/- 0.0063 mm)
Repeatability	0.0002" (0.005 mm)
Axis Thrust Force X, Z	1500 lbs. (680 kg)

GENERAL:

Machine Height	80" (2032 mm)
Floor Space Required (W x D)	120 x 83" (3050 x 2110 mm)
Machine Weight	6000 lbs. (2730 kg)
Power Required	23 KVA /60 amps
Voltage Required	208-240 Volts / 3 Phase

MACHINE STANDARDS:

- Milltronics 8200-B series CNC control
- Solid box way bed construction
- 4000 RPM spindle
- Tailstock
- Auto lubrication
- Full enclosure w/ sliding doors
- 2.04" Spindle bore
- A2-5 Spindle nose
- 12" LCD color display
- Spindle load meter
- Flood coolant
- Solid model graphic display
- USB Port
- Gap bed design
- 8 Station 3/4" automatic turret
- LCD hour meter
- Thread chasing feature
- One year warranty
- Constant Surface Speed (CSS)



8200-B CNC

The new standard of control

With its conversational programming, onscreen help, intuitive menus, color graphics and prompted tool settings, the 8200-B CNC helps new operators train faster and become more productive sooner. Shops can choose either conversational, G-code programming, or download tool paths created with a CAM system - whatever is the most efficient way to produce the required part.

CONTROL STANDARDS:

- PC-based 8200-B CNC includes 1 GB parts storage memory
- Enhanced CPU with Block processing speed of 2000 bps with enhanced jerk control and look ahead
- Conversational plus G & M code programming including coordinate rotating, scaling, mirror image, thread mill engraving, helical interpolation, auto routines, and user definable macros with trig assist and irregular pocket clearing
- 12" LCD active matrix color display
- Auto DXF file import
- 3D part and wire frame tool path graphics plus solid modeling graphics
- Management software that allows editing of very large programfiles at the machine
- Spindle loader meter
- User definable macros with trig assist
- USB connectivity
- MTConnect compliant
- Networking

Distributed By: