SteakFest 2024 Open House May 14-15 in Delafield, WI

Machine tool and metrology technology, over 40 machines with demos, automation, tooling partners, and inspection services. 10:00am - 7:00pm each day!



In conjunction with the open house, Concept is offering the following educational seminars:

Tuesday, May 14, 2024

11:00AM - 12:00PM How OEMs and job shops benefit from the reshoring trend - by Harry C. Moser, President, Reshoring Initiative

1:00PM - 2:00PM Automation - What are my options?

3:00PM - 4:00PM Introduction to Swiss-style machining Wednesday, May 15, 2024 10:00AM - 11:15AM Introduction to Swiss-style machining

1:00PM - 2:00PM When should I consider a Horizontal Machining Center? HMC vs VMC.



Register at <u>conceptmachine.com/events/</u> or scan the code:

Production CNC



Kitamura 2XV Sparkchanger w/automation

- Vertical machining center
- Travels: X 23.6", Y 20.1", Z 20.1"
- Spindle: 15,000 RPM, 41 HP, #40
- ATC: 40 tool standard

Also displaying: Kitamura Mycenter-4XV and Kitamura HX250iG HMC.



C22U - 5-Axis

- Mineral base casting
- 18,000/24,000 RPM spindle
- HSK40 or HSK63 spindle
- Drop trunnion tables near perfect ergonomics
- 31.5" x 25" rotary table
- Flex pallet system for robotic automation

TAKAMAZ



Takamaz XY-120 Plus

- Spindle speed 4,000 RPM
- A2-6 main spindle with 2" bar capacity, A2-5 sub-spindle
- 12-station upper turret with Y-axis
- 12-station static lower turret

Also displaying: Takamaz XT-6



Kira PCV-30

- Vertical production center
- XYZ travels: 19.7" x 11.8" x 11.8"
- 10,000 RPM, BTD 30 spindle
- Rigid tapping, 4,000 RPM
- FANUC control



- Swiss-type lathe w/38mm capacity
- 10 station turret
- 7,000 RPM main and sub-spindle .
- 8-spindle back-working unit







SMEC SL2500BSY w/Halter

- 10" chuck lathe (3" bar capacity)
- Heavy duty box way construction
- 12 station BMT turret (24 position)
- Displayed with Halter Universal robot loader



SMEC MCV-6700L

- Vertical machining center with X 82.7", Y 26.4", Z 20.5" travels
- Spindle: 12,000 RPM direct drive
- CAT40 (Big Plus)
- 30 tool ATC
- FANUC control



Fuji CSD-300II

- Twin spindle, twin turret lathe
- Spindle speed 4,000 RPM
- 8" 10" workholding .
- FANUC control
- 10 station per turret (x2)

Tool Room & EDM





Milltronics VM4020

- Vertical machining center with X 40", Y 20", Z 20" travels
- Highly-intuitive Conversational Control

Also displaying: Milltronics VM3020IL



Milltronics ML18/60 Combination lathe with 19" swing



Supertec G25P-50CNC Plunge type cylindrical grinder



Chevalier FSG1224 ADIV Surface Grinder

CHEVALIER

Chevalier FRG-600S Rotary Grinder





MITSUBISHI EDM

Mitsubishi MV1200S Wire EDM

- 10-year positioning accuracy guarantee
- Automatic Wire Threading (AT)
- Linear Scales X, Y, U, V axis
- Wire savings of 40% with the V350 power supply
- Remote 360 monitoring
- Three sizes of machine models





EDM Drillmate DMC4030

- Travels 15.7" X, 11.8" Y, 14" Z
- Granite table 17.7" x 15.3"
- Programmable W-axis option
- Standard touch screen
- Tapping option

Automation Solutions

HALTER FANUC Robot



Halter Load Assistant

Turning or Milling retrofit

- Mobile package
- Touch Screen Smart easy programming Easy quick change gripper
- Easy quick change gripper system (Opt10/20)

FANUC CRX 10iA



Applications

- Load/Unload
- Machine Tending
- Part Inspection
- Pick and Place
- Packing
- Palletizing
- And more!

Metrology & Precision Inspection





ZEISS Contura CMM for measuring complex features and parts.



ZEISS O-inspect 543 Premium sensors for leading edge optical and contact performance.



ZEISS Surfcom NEX Hybrid CNC Profilometer.



ZEISS Rondcom NEX Form measurement system.



ZEISS

ZEISS Metrotom Large format CT.



ZEISS Atos Q Industrial 3D scanner.



ZEISS T-Scan Hawk 2 3D laser scanner.



MICRO-VU Vertex CNC vision measurement system.



Starrett HDV400 Horizontal digital video comparator.



Shaft measurement system.




Metri OS HD Cross Optical measuring for micro-components.



FANUC Robotics **CRX-10iA** Collaborative robot for automated tending of metrology equipment.





High speed dual camera measurement & sorting system.